

Electronic control

extremely intuitive and easy-to-use even by less skilled staff

Three-point door locking system

Available power

installed power is perfectly calibrated to the usage



Humidifier

designed to minimize the water consumption

Periodic and automatic rotation reversal of the fan motors

allows the perfect temperature uniformity in the cavity

Tight-sealed cavity

the rounded corners and the integrated drainage system make cleaning easier and safer

Stainless steel bumpers

positioned within the cavity allow a safer introduction of the tray or dish-holder trolleys

Cavity

at floor level, facilitates manoeuvres in the kitchen with the tray or dish-holder trolleys



RRFF/RRFT SERIES



RRFF20E

RRFF22E

RRFT20E

RRFT22E

Trays capacity	20 GN 1/1 ¹	20 GN 1/1 ¹	20 GN 1/1 ²	20 GN 1/1 ^{2,3}
Dishes capacity	80 (ø from 180 mm to 310 mm)	80 (ø from 180 mm to 310 mm)	80 (ø from 180 mm to 310 mm)	80 (ø from 180 mm to 310 mm)
Operating temperature	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C
Cavity dimensions	780x695x1860 mm	780x705x1860 mm	570x805x1860 mm	570x815x1860 mm
Electric power	12500 W	12500 W	12500 W	12500 W
Electric supply	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz
Dimensions	1150x830x1950 mm	1150x830x1950 mm	940x940x1950 mm	940x940x1950 mm

1. Tray introduction from the narrow side

2. Tray introduction from the wide side

3. The pass through version allows the trolley introduction on both sides

RRFF SERIES



RRFF40E



RRFF42E

Trays capacity	40 GN 1/1 or 20 GN 2/1 ¹	40 GN 1/1 or 20 GN 2/1 ^{1,2}
Dishes capacity	126 (ø from 180 mm to 310 mm)	126 (ø from 180 mm to 310 mm)
Operating temperature	from +30°C to +160°C	from +30°C to +160°C
Cavity dimensions	780x965x1860 mm	780x975x1860 mm
Electric power	23000 W	23000 W
Electric supply	400 Vac 3N 50Hz	400 Vac 3N 50Hz
Dimensions	1150x1100x1950 mm	1150x1100x1950 mm

1. Tray introduction from the wide side

2. The pass through version allows the trolley introduction on both sides

RRD/RRFC SERIES



RRD061E

RRD101E

RRFC20E

RRFC40E

Trays capacity	6 GN 1/1 or 600x400	10 GN 1/1 or 600x400	20 GN 1/1	40 GN 1/1 or 20 GN 2/1
Dishes capacity	12 (ø max. 280 mm)	20 (ø max. 280 mm)	80 (ø max. 280 mm)	126 (ø max. 280 mm)
Tray rails pitch	75 mm	75 mm	–	–
Operating temperature	from +0°C to +160°C	from +0°C to +160°C	from +0°C to +160°C	from +0°C to +160°C
Cavity dimensions	–	–	780x695x1860 mm	780x975x1860 mm
Electric power	4000 W	7000 W	13500 W	24300 W
Electric supply	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz
Dimensions	890x815x1340 mm	890x815x1640 mm	1150x830x2270 mm	1150x1100x2270 mm

These are also cold holding units