

# RRT SERIES



	RRT061C/D/E	RRT101C/D/E	RRT161C/D/E	RRT112C/D/E	RRT153C/D/E	RRT162C/D/E
Trays capacity	6 (GN 1/1 or 600x400) <sup>1</sup>	10 (GN 1/1 or 600x400) <sup>1</sup>	16 (GN 1/1 or 600x400) <sup>1</sup>	10 GN 2/1 or 20 GN 1/1 <sup>2</sup>	16 GN 2/1 or 32 GN 1/1 <sup>2</sup>	16 GN 2/1 <sup>1</sup>
Dishes capacity	12 (ø max 280)	20 (ø max 280)	32 (ø max 280)	40 (ø max 280)	64 (ø max 280)	88 (ø max 280)
Tray rails pitch	75 mm	75 mm	72 mm	76 mm	72 mm	79 mm
Operating temperature	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C
Electric power	3200 W	6500 W	6500 W	6500 W	9600 W	9600 W
Electric supply	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz
Dimensions	890x815x1010 mm	890x815x1310 mm	890x815x1820 mm	1010x855x1130 mm	1010x855x1680 mm	950x965x1920 mm

1. Tray introduction from the narrow side

2. Tray introduction from the wide side