

RRO SERIES



	RRO051C/D/E RRO061C/D/E	RRO081C/D/E RRO101C/D/E	RRO111C/D/E RRO141C/D/E	RRO062C/D/E RRO072C/D/E	RRO082C/D/E RRO102C/D/E	RRO112C/D/E RRO142C/D/E
Trays capacity	5/6 (GN 1/1 or 600x400)	8/10 (GN 1/1 or 600x400)	11/14 (GN 1/1 or 600x400)	6/7 GN 2/1	8/10 GN 2/1	11/14 GN 2/1
Dishes capacity	10/12 (ø max 280)	16/20 (ø max 280)	22/28 (ø max 280)	24/28 (ø max 280)	32/40 (ø max 280)	44/56 (ø max 280)
Tray rails pitch	90/75 mm	90/75 mm	90/75 mm	90/75 mm	90/75 mm	90/75 mm
Operating temp.	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C	from +30°C to +160°C
Electric power	6200 W	12500 W	16000 W	12500 W	16000 W	23000 W
Electric supply	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz	400 Vac 3N 50Hz
Dimensions	800x710x855 mm	800x710x1155 mm	800x710x1650 mm	860x860x935 mm	860x860x1155 mm	860x860x1650 mm