

SCROLL COMPRESSORS



Compressor	Capacity (kW) at*				Application (T. evap °C)	Displacement m³/h	CV	PVP 2017
	-5/+45°C	-10/+45°C	-25/+45°C	-30/+45°C				
ZS4084S1	1,10	0,92	0,49	0,39	-45°C a +10°C	1,51	1/2	856 €
ZS7516S1	1,99	1,69	0,95	0,76	-45°C a +10°C	2,86	1	882 €
ZS1120S1	2,73	2,32	1,31	1,05	-45°C a +10°C	3,62	1 1/2	1.576 €
DS1529S1	3,46	2,92	1,62	1,30	-45°C a +10°C	5,03	2	1.591 €
DS1836S1	4,26	3,55	1,92	1,54	-45°C a +10°C	6,43	2 1/2	1.601 €
DS2244V1	4,85	4,13	2,36	1,91	-45°C a +10°C	7,92	3	1.926 €
FL300DL	7,07	5,92	3,30	2,66	-45°C a +5°C	10,08	3 1/2	3.412 €
FL400DL	9,14	7,65	4,27	3,44	-45°C a +5°C	12,91	4	3.632 €
FL500DL	11,48	9,60	5,35	4,31	-45°C a +5°C	16,20	5	3.843 €

*for R-407A; R-407C; R-407F; R-404A; R-507; R-448A; R-449A (for R-134a and R-450A at -10°C, multiply by 0,57)



Compressor	Capacity (kW) at*				Application (T. evap °C)	Displacement m³/h	CV	PVP 2017
	-5/+45°C	-10/+45°C	-25/+45°C	-30/+45°C				
C-SBN263H8A	7,49	6,01			-25°C a +15°C	10,03	3,5	860 €
C-SBN303H8A	9,08	7,28			-25°C a +15°C	12,02	4	869 €
C-SBN373H8G	11,35	9,10			-25°C a +15°C	14,98	5	902 €
C-SBN453H8G	13,75	11,05			-25°C a +15°C	18,00	6	913 €
C-SBS235H38B	15,35	12,24			-25°C a +15°C	19,84,	7	1.026 €
C-SCN603H8K	19,28	15,38			-25°C a +15°C	24,66	8	1.699 €
C-SCN753H8K	23,41	18,77			-25°C a +15°C	30,82	10	1.776 €
C-SCN903H8K	27,29	21,90			-25°C a +15°C	36,97	12	1.890 €
C-SCN453L8H			5,16	6,25	-45°C a -5°C	18,72	6	2.941 €
C-SCN603L8H			6,50	7,92	-45°C a -5°C	24,66	8	3.048 €
C-SCN753L8H			7,61	9,63	-45°C a -5°C	30,82	10	3.146 €

*for R-407A; R-407C; R-407F; R-404A; R-507; R-448A; R-449A (for R-134a and R-450A a -10°C, multiply by 0,57)